

■ C-band 2W BUC

MODEL No. **NJT5667/68/74** series

< Features >

- * **High Efficiency Output Power**
 •P1dB: +33 dBm min. over temperature
- * **Low Power Consumption**
 •Power Consumption: 33 W
- * **Small Size & Light Weight**
 •Weight: 1.9 kg
- * **LED Indicator**
- * **RoHS Compliance**



< Line-Up >

Model No.	RF Frequency	Local Frequency	IF Frequency	Output Power @ P1dB	IF Connector	Power Supply	LED Indicator
NJT5667	5.85 to 6.425 GHz (Standard C-band)	4.90 GHz	950 to 1,525 MHz	2W Linear (+33 dBm min.)	N-type	+24 VDC (+15 to +30 VDC)	Equipped
NJT5667F					F-type		
NJT5674N	6.365 to 6.725 GHz (Palapa C-band)	5.30 GHz	1,065 to 1,425 GHz		N-type		
NJT5674F					F-type		
NJT5668	6.725 to 7.025 GHz (Insat C-band)	5.76 GHz	965 to 1,265 GHz		N-type		
NJT5668F					F-type		

< Specifications >


Item	Specifications
Output Interface	Waveguide, CPR137 (with Groove)
Input Interface	N-type, female (50 ohm) [Model No.: NJT5667/68/74N] F-type, female (75 ohm) [Model No.: NJT5667F/68F/74F]
Output Power @ 1 dB G.C.P.	+33 dBm min. over temperature
Linear Gain	58 dB nom.
Requirement for External Reference	[Frequency] 10 MHz (sine-wave) [Input Power] -5 to +5 dBm @ Input port [Phase Noise] -120 dBc/Hz max. @ 100 Hz -130 dBc/Hz max. @ 1 kHz -140 dBc/Hz max. @ 10 kHz -150 dBc/Hz max. @ 100 kHz
L.O. Phase Noise	-60 dBc/Hz max. @ 100 Hz -70 dBc/Hz max. @ 1 kHz -80 dBc/Hz max. @ 10 kHz -90 dBc/Hz max. @ 100 kHz
Receive Band Noise Density	-87 dBm/4kHz max.
Input V.S.W.R.	2.0 : 1 max.
Output V.S.W.R.	2.0 : 1 max.
Power Requirement	+24 VDC (+15 to +30 VDC)
Power Consumption	33 W max.
Mute	Shut off the HPA in case of L.O. unlocked or no 10 MHz reference signal.
LED Indicator	GREEN: L.O. locked / RED: L.O. unlocked or no 10 MHz reference signal
Temperature Range (ambient)	-40 to +55 C (operating), -40 to +75 C (storage)
Dimension & Housing (without Interface Connectors)	190.6 mm (L) x 160 mm (W) x 59 mm (H) [7.50" (L) x 6.30" (W) x 2.32" (H)]
Weight	1.9 kg [4.2 lbs]

■ C-band 2W BUC

MODEL No. **NJT5667/68/74** series

< Outline Drawing >

NJT5667/68/74N



■ C-band 2W BUC

MODEL No. **NJT5667/68/74** series

< Outline Drawing >

NJT5667F/68F/74F

